

The enhanced machine model for wide strapping



Characteristics

Strapping qualities:	Polypropylene (PP)	
Strapping dimensions:	widths	8.0 – 12.0 mm
	thicknesses	0.55 – 0.75 mm
Strapping tension:	adjustable, 70 – 700 N	
Sealing method:	heat welding	
Power supply:	230V / 50Hz, 1 phase	
Power consumption:	1.2 kWh	
Strapping speed:	2.1 sec./cycle (approx. 29 strapping cycles/min.)	
Dimensions:	length	1430 mm
	width	620 mm
	table height	810 mm
Machine net weight:	220 kg	
Max. package weight:	100 kg	
Min. package size:	130W x 20H mm	
Arch size:	850 x 600 mm standard	
Temp. of working environment:	5 ~ 40°C	

Advantages

- Proven quality
- Competitive price
- CE certified
- Bundles and cartons can be strapped very easily and quickly
- User-friendly and easy strapping coil change
- Easy operation, simple maintenance
- Electronic outside tension control
- Tension can be easily set with a dial
- Mobile, on wheels with brakes
- Auto strap reefed
- Strap end ejector
- Short feed sensor and foot switch included

Chart of types model PM309

Item No.	Arch size W x H (mm)	Strap width	Colour
45.4111	650 x 400	9.00 mm	blue
45.4112	650 x 400	12.0 mm	blue
45.4121	850 x 600	9.0 mm	blue
45.4122*	850 x 600	12.0 mm	blue
45.4131	1050 x 800	9.0 mm	blue
45.4132*	1050 x 800	12.0 mm	blue
45.4141	1250 x 1000	9.0 mm	blue
45.4142	1250 x 1000	12.0 mm	blue

* Machines in stock, NL-Nieuwegein.
Availability other machines upon request.
Different arch sizes possible.